

CONIX MONO – Product Range

Diameters up to 600mm			
T600-H1-W-V2-L50040-G(75) with insulation , enclosed in a shaft;			
T450-N1-D-V2-L50040-G(75) with insulation , enclosed in a shaft;			
T200-P1-W-V2-L50040-O(30)			
TERMINAL PART			
KI 060: Tapared Terminal	■	■	■
KI 061: Anti-Backflow Terminal	■	■	■
KI 062: Rain cap	■	■	■
STRAIGHT CHIMNEY ELEMENT			
KI 090/KI190: Straight chimney section for relining	■	■	■
KI 091: Straight chimney section (944mm)	■	■	■
KI 093: Straight chimney section (444mm)	■	■	■
KI 194: Straight chimney section (194mm)	■	■	■
KI 095: Straight chimney section	■ (1)	■	
INSPECTION ELEMENT			
KI 072: Inspection element with plug (T600-H1-W)	■	■	■
KI 097: Element with hole for measurement devices	■	■	■
KI N98: Inspection element with plug (T450-N1-D)		■	
KI P98: Inspection element with plug (T200-P1-W)	■ (1)		
TEE			
KI 066: Tee reduced to 80mm	■ (1)		
KI 067: Tee reduced to 80mm with nipple for the measurement device	■ (1)		
KI 070: Tee 90°	■	■	■
KI 170: Tee 87°	■	■	■
KI 071: Tee 45°	■	■	■
ELBOW			
KI 073: Elbow 15°	■	■	■
KI 074: Elbow 30°	■	■	■
KI 075: Elbow 45°	■	■	■
KI 076: Elbow 87	■	■	■
KI 078: Elbow 90°	■	■	■
KI 017: Elbow 0-90°		■	
KI G17: Elbow 0-90° with seal	■ (1)		
STARTING ELEMENTS			
KI 077: Condensate Drain	■	■	■
KI 082: Middle Plate	■	■	■
CONNECTION ELEMENT			
KI 009 : Joint Element (KI – NI)	■	■	■
KI 024 : Joint element Di (Female) - 60mm (Sleeve)	■	■	■
KI 025 : Joint element Di (Female) - 80mm (Sleeve)	■	■	■
KI 026: Joint element Di (Female) - 100mm (Sleeve)	■	■	■
KI 096: Joint Element	■	■	■
KI 009 : Joint Element (KI – NI)	■	■	■
ACCESSORY			
KI 013: Element with condensate drain	■	■	■
KI 019: Pressure Equalising Opening	(n.a.)	(n.a.)	(n.a.)
KI 033: Plug for Cascade Arrangement	■	■	■

(1): mit sylcondichtung
(n.a.): Nicht anwendbar

CONIX MONO – Product Range

Diameters more than 60mm			
T600-P2-W-V2-L50040-G(75) with insulation , enclosed in a shaft;			
T450-N1-W-V2-L50040-G(75) with insulation , enclosed in a shaft;			
T200-P2-W-V2-L50040-O(30)			
STRAIGHT CHIMNEY ELEMENT			
KI 090/KI190: Straight chimney section for relining	■	■	■
KI 091: Straight chimney section (944mm)	■	■	■
KI 093: Straight chimney section (444mm)	■	■	■
KI 194: Straight chimney section (194mm)	■	■	■
KI 095: Straight chimney section	■ ⁽¹⁾	■	
INSPECTION ELEMENT			
KI 072: Inspection element with plug (T600-H1-W)	■	■	■
KI 097: Element with hole for measurement devices	■	■	■
KI N98: Inspection element with plug (T450-N1-D)		■	
KI P98: Inspection element with plug (T200-P1-W)	■ ⁽¹⁾		
TEE			
KI 170: Tee 87°	■	■	■
ELBOW			
KI 073: <i>Bogen</i> 15°	■	■	■
KI 074: <i>Bogen</i> 30°	■	■	■
KI 042: <i>Bogen</i> 42°	■	■	■
KI 075: <i>Bogen</i> 45°	■	■	■
KI 076: <i>Bogen</i> 87°	■	■	■
KI 017: <i>Bogen</i> 0-90° drehbar, ohne dichtung		■	
KI G17: <i>Elbow</i> 0-90° drehbar, mit dichtung	■ ⁽¹⁾		
STARTING ELEMENT			
KI 077: Condensate Drain	■	■	■
KI 082: Middle Plate	■	■	■
CONNECTION ELEMENT			
KI 009 : Joint Element (KI – NI)	■	■	■
KI 024 : Joint element Di (Female) - 60mm (Sleeve)	■	■	■
KI 025 : Joint element Di (Female) - 80mm (Sleeve)	■	■	■
KI 026: Joint element Di (Female) - 100mm (Sleeve)	■	■	■
KI 096: Joint Element	■	■	■
ACCESSORY			
KI 013: Element with condensate drain	■	■	■
KI 033: Plug for Cascade Arrangement	■	■	■

⁽¹⁾: with seal

(n.a.): not applicable

CONIX MONO – Product Range

